



**CATEGORY 1**

# STORM SYSTEM®



**1120 - Transparent Waterproofer** Storm System Waterproofer is a transparent sealer that penetrates the surface of dry, porous wood surfaces to help prevent moisture penetration and water damage. This product dries clear and allows the wood surface to age naturally. This product will protect against saltwater. For new construction, prevent water damage by applying this product immediately after installation. **Recommended Use:** Shingles, Shakes, Siding, Fencing, Decks, Rails, Outdoor Furniture and Storage Sheds.



**11540 - Transparent Dual Dispersion** Dual Dispersion technology offers one-coat application blending the best features of traditional Oil-based finishes and Acrylic paints. This natural clear finish for wood has excellent flow, leveling and durability of oil-based paint and the fast-dry time and soap and water clean-up of latex paint. Dual Dispersion Clear Finish resists cracking, peeling blistering and moisture. It is environmentally friendly and low VOC\*. Meets federal specification TFW572B par 3.7 for water repellency. **Recommended Use:** Hardwood, Pressure Treated, Conventional and Exotic Hardwoods, Sun Decks, Wood Screening, Patios, Siding, Fencing, Benches, Walkways & Outdoor Furniture.



**11024 - Transparent Wood Life Extender** Storm System Wood Life Extender has been developed to prolong the life of wood and wood products. This clear zinc naphthenate is designed to retard warping, swelling, shrinking and checking of previously unfinished woods. This product repels moisture and resists the growth of mildew and other fungus on the cured surface. Wood surfaces protected with this product will be affected by UV light unless top coated with pigmented paints or stain systems. This product can be re-coated after 24 hours with either latex or stain systems. **Recommended Use:** Unfinished Wood Decks, Timber, Sills, Architectural Millwork, Window Sash, Gutters, Siding Plywood & Canvas.



**11550 - Transparent 100% Acrylic Topcoat** 100% acrylic latex clear topcoat can be used alone, or in conjunction with Category 2 & 3 Dual Dispersion Storm System stains. This premium formula is the ideal clear finish designed to protect the beauty and longevity of wood finishes derived from Category 2 & 3 Dual Dispersion products and can also be used as a maintenance coat to refresh the look after surfaces weather. 100% Acrylic Topcoat resists mildew\*, cracking and repels moisture. This clear protective coating is environmentally friendly featuring low VOC formula. **Recommended Use:** Pressure Treated and Conventional Woods, Sun Decks, Wood Screening, Patios, Siding, Fences, Benches, Outdoor Furniture, Railing and Posts.



**10040/NR10040\* - Transparent Natural Oil Stain** Storm System Natural Oil Finish provides maximum protection to exterior wood decks and surfaces exposed to water, ultraviolet rays and general atmospheric contamination including acid rain. This durable resin seals, waterproofs and protects exterior wood decks subject to the rigors of drastic weather and temperature changes. This finish restricts cracking, peeling and blistering and can be used on new wood, previously stained wood and new pressure treated wood with proper preparation. One coat should be applied over new or previously stained or finished decks that have aged and have been properly prepared. This finish has a honey color and is formulated for maximum abrasion on high traffic areas. **Recommended Use:** Decks, Fencing, Railings, Posts, Wood Enclosures, Benches, Patios, Outdoor Furniture.

Available Colors & Sizes	1120			11024			10040			NR10040*			11540			11550		
	Qt	Gal	5 Gal	Qt	Gal	5 Gal	Qt	Gal	5 Gal	Qt	Gal	5 Gal	Qt	Gal	5 Gal	Qt	Gal	5 Gal
Clear		•	•		•			•			•	•		•			•	



**CATEGORY 1** **STORM SYSTEM®**

**Category 1 - Clears, Waterproofers and Sealers**

Opacity	Number	Product Type	Spread Rate	Dry Time	VOC Compliance
Clear	10040	Alkyd	Smooth surface 300-350 sq ft/gal; Porous surface 200-250 sq ft/gal	To touch 4-6 hours, to handle 6 hours, to recoat 24 hours, to clean 48 hours	EPA AIM, LADCO, OTC I, Canada AIM
Clear	NR10040*	Alkyd	Smooth surface 300-350 sq ft/gal; Porous surface 200-250 sq ft/gal	To touch 4-6 hours, to handle 6 hours, to recoat 24 hours, to clean 48 hours	EPA AI
Clear	11020	Carboxylate Complex	Smooth surface 300 sq ft/gal; Porous surface 90 sq ft/gal	To touch N/A hours, to handle N/A hours, to recoat .5-6 hours	EPA AIM, CARB, SCAQM, LADCO, OTC I, OTC II, Canada AIM
Clear	11024	Alkyd	Smooth surface 125-175 sq ft/gal; Porous surface 100-150 sq ft/gal	To touch 24 hours, to handle 24 hours	EPA AIM, CARB, SCAQM, LADCO, OTC I, OTC II, Canada AIM
Clear	11540	Acrylic/Alkyd Dispersion	Smooth surface 200-400 sq ft/gal; Porous surface 150-350 sq ft/gal	To touch 4 hours, to handle 6 hours, to recoat 8 hours	 EPA AIM, CARB, SCAQM, LADCO, OTC I, OTC II, Canada AIM
Clear	11550	100% Acrylic Latex	Smooth surface 200-400 sq ft/gal; Porous surface 150-350 sq ft/gal	To touch 4 hours, to handle 4-6 hours, to recoat 16 hours	EPA AIM, CARB, SCAQM, LADCO, OTC I, OTC II, Canada AIM

\* NR versions of items can not be sold in the following states: CA, CT, DC, DE, IL, IN, MA, MD, ME, NH, NJ, NY, OH, PA, RI, UT, VA

Transparent Dual Dispersion is certified by Coating Research Group Inc. to meet performance and environmental standards as shown on [www.greenwisepaint.com](http://www.greenwisepaint.com). The addition of VOC-containing colorants may increase the final VOC of a tinted paint.

§This product meets odor testing standards in order to achieve Green Wise Certification by the Coating Research Group Inc. CRGI Test Method 78.

‡Contains an additive designed to inhibit growth of mold and mildew on the dried paint film only.

 <p><b>California</b> PAINTS</p> <p>Interior and exterior architectural coatings for consumer and professional application.</p>	 <p><b>FIX ALL</b> SINCE 1883</p> <p>Surface-specific specialty paint and coatings solutions.</p>	 <p><b>STORM</b> SYSTEM</p> <p>Exterior wood care products and stains for every condition.</p>
--	--	---

ICP Building Solutions Group offers a comprehensive range of building products along with class-leading cementitious and sports surfacing systems. Build on the foundation of innovations that improve®, ICP offers building solutions that set the standard in their markets and present unparalleled value to our customers.

**STORM SYSTEM IS A BRAND OF:**



150 Dascomb Rd., Andover, MA 01810  
978.623.9980 • [www.icpgroup.com](http://www.icpgroup.com)