



CATEGORY

3

STORM
SYSTEM®



34095/NR34095* - Semi-Solid Alkyd Linseed Oil Stain
Storm System Alkyd Linseed Oil Finish Semi-Solid Clear Base is rich in linseed oil is designed to provide years of service and beauty for most exterior wood surfaces. The partial pigmentation of this finish blends with the colors and tones of the wood without distracting from the natural graining and texture inherent in the wood itself. Semi-Solid linseed oil base finish repels water and provides maximum protection from the ravages of weather. This product contains wood preservatives which help protect the film against mildew, fungus and moisture on properly prepared wood. **Recommended Use:** Shingles, Trim, Shakes, Fences, Clapboards, Plywood, Decks.




34595 - Semi-Solid Dual Dispersion Basecoat Water Reducible Alkyd Storm Category 3 Dual Dispersion Semi-Solid Clear Base Boasts State of the art low VOC* Dual Dispersion technology to provide the best features of traditional oil-based paints and latex paints. As a finish it has the excellent flow, leveling and durability of oil-based paint with the fast-dry time and soap and water clean-up of latex paint. Dual Dispersion Semi-Solid Clear Base resists cracking, peeling blistering and moisture. This product can be used on multiple wood surfaces including dense hardwoods such as mahogany, teak and fir. This product can be applied over new or previously stained or finished woods that have aged and have been properly prepared. **Recommended Use:** Pressure Treated and Conventional Woods, Sun Decks, Wood Screening, Patios, Siding, Fencing, Benches & Porches.

| Available Colors & Sizes | 34095 | | | NR34095 | | | 34595 | | |
|--------------------------|-------|-----|-------|---------|-----|-------|-------|-----|-------|
| | Qt | Gal | 5 Gal | Qt | Gal | 5 Gal | Qt | Gal | 5 Gal |
| Clear 95 | • | • | • | • | • | • | • | • | |



STORM
SYSTEM®

Category 3 - Semi-Solid Exterior Stains

| Opacity | Number | Product Type | Spread Rate | Dry Time | VOC Compliance |
|------------|----------|--------------------------|---|--|---|
| Clear Base | 34095 | Alkyd Linseed Oil | Smooth surface 325-400 sq ft/gal; Porous surface 200-250 sq ft/gal | To touch 4-6 hours, to handle 12-16 hours | EPA AIM, LADCO, OTC I, Canada AIM |
| Clear Base | NR34095* | Alkyd Linseed Oil | Smooth surface 325-400 sq ft/gal; Porous surface 200-250 sq ft/gal | To touch 4-6 hours, to handle 12-16 hours | EPA AIM |
| Clear Base | 34595 | Acrylic/Alkyd Dispersion | Smooth surface 200-400 sq ft/gal; Porous surface 150-350 sq ft/gal | To touch 4 hours, to handle 6 hours, |  EPA AIM, CARB, SCAQM, LADCO, OTC I, OTC II, Canada AIM |

* NR versions of items can not be sold in the following states: CA, CT, DC, DE, IL, IN, MA, MD, ME, NH, NJ, NY, OH, PA, RI, UT, VA

Semi-Solid Dual Dispersion is certified by Coating Research Group Inc. to meet performance and environmental standards as shown on www.greenwisepaint.com. The addition of VOC-containing colorants may increase the final VOC of a tinted paint.

§This product meets odor testing standards in order to achieve Green Wise Certification by the Coating Research Group Inc. CRGI Test Method 78.



Interior and exterior architectural coatings for consumer and professional application.



Surface-specific specialty paint and coatings solutions.



Exterior wood care products and stains for every condition.

ICP Building Solutions Group offers a comprehensive range of building products along with class-leading cementitious and sports surfacing systems. Build on the foundation of innovations that improve®, ICP offers building solutions that set the standard in their markets and present unparalleled value to our customers.

STORM SYSTEM IS A BRAND OF:



150 Dascomb Rd., Andover, MA 01810
978.623.9980 • www.icpgroup.com

Rev. 07.24.19