



523XX - Extreme Conditions Quick-Dry Oil Primer
 Designed to be used under white and light solid colored stains to inhibit extractive bleeding and provide a long-lasting finish. This neutralizes and helps eliminate the natural tannin or sugar staining and discoloration produced by bare woods such as red cedar, redwood, fir, pine or white cedar, and seals the wood for uniformity of the finish. This primer helps to diminish the surface rusting of uncoated nails. **Recommended Use:** Shingles, Trim, Shakes, Fences, Clapboards, Plywood, Decks.




543XX - Extreme Conditions Acrylic Latex Primer
 This exterior base coat is designed to help eliminate the natural tannin, sugar staining and discoloration produced by many types of bare wood. Storm System Acrylic Latex Primer has a unique moisture-transmitting formulation that provides excellent adhesion to properly prepared wood surfaces and is highly resistant to peeling. **FOR VERTICAL SURFACES ONLY. Recommended Use:** Sundecks, railings and posts, fences, benches, trellis, wood walkways, open porches, wood screening, patios, garden enclosures, outdoor furniture and siding.

Available Colors & Sizes	523XX			543XX		
	Qt	Gal	5 Gal	Qt	Gal	5 Gal
White Primer 00		•	•		•	
Clear Base 95		•	•		•	



Category 5 - Exterior Primers

Opacity	Number	Product Type	Spread Rate	Dry Time	VOC Compliance
White / Clear	523XX	100% Acrylic Latex	Smooth surface 325-400 sq ft/gal; Porous surface 250-325 sq ft/gal	To touch 4 hours, to handle 4 hours to recoat: 6 hours	EPA AIM, LADCO, OTC I, Canada AIM
White / Clear	543XX	Alkyd Linseed Oil	Smooth surface 400-450 sq ft/gal; Porous surface 375-425 sq ft/gal	To touch 1 hours, to handle 4 hours to recoat: 4 hours	 EPA AIM, CARB, SCAQM, LADCO, OTC I, OTC II, Canada AIM

Extreme Conditions Acrylic Latex Primer is certified by Coating Research Group Inc. to meet performance and environmental standards as shown on www.greenwisepaint.com. The addition of VOC-containing colorants may increase the final VOC of a tinted paint.

§This product meets odor testing standards in order to achieve Green Wise Certification by the Coating Research Group Inc. CRGI Test Method 78.



Interior and exterior architectural coatings for consumer and professional application.



Surface-specific specialty paint and coatings solutions.



Exterior wood care products and stains for every condition.

ICP Building Solutions Group offers a comprehensive range of building products along with class-leading cementitious and sports surfacing systems. Build on the foundation of innovations that improve®, ICP offers building solutions that set the standard in their markets and present unparalleled value to our customers.

STORM SYSTEM IS A BRAND OF:



150 Dascomb Rd., Andover, MA 01810
978.623.9980 • www.icpgroup.com

Rev. 07.24.19